



Document/File name DSC203834E	Document Type External	Revision 1
First Revision, Sign and Date Bln 2018-10-01	Updated Revision, Sign and Date	Document Status and Sign Approved Lan
Document and Product Description Description RFD360-5KP Pnr. 20-383-4		Page 1 (1)

Part # 20-383-4

RFD360 Contactless transmissive 360 degrees Rotary sensor with a fitted waterproof SureSeal connector. The RFD360 sensor have an unlimited mechanical lifetime and is normally used as a barrel sensor on sequential gearboxes. Directly connects to both TTT802 Gearshift Controller and TTT031 Gear Indicator cable harness.



RFD360-5KP	Aprox: 0,45 m	3-pole SureSeal Female
------------	---------------	------------------------

Weight:

RFD360-5KP 28 grams
Position Marker 4 grams

Position marker (magnet)

Z-RFC-P04 / Z-RFC-P03, are sold separately with its own part number.

Connector: 3-pole SureSeal Female

Marking: Pnr & Snr Length: 30mm
Clear crimp tube over marking length: 45mm Type: 6 / 2
Crimp tube length: 450mm Type: DR25 4,8 / 2,4
Crimp tube length: 30mm Type: ATUM 9 / 3

Black – con 1 (socket) - Gnd
Red – con 2 (pin) - + 5 Volt
Blue – con 3 (pin) - Signal

